

HANGZHOU HANHAO CHEMICAL CO., LTD

Plant: Jiangdong Development Zone, Great Jiangdong District, Hangzhou China

Office: 2103 Bldg1, Dacheng Plaza, Shixin Road, Xiaoshan, Hangzhou, China

Tel:+86-571-82502631/82551631 **Fax:**+86-571-82722631

TECHNICAL DATA SHEET

Product Description:

Product Name:	Fast Yellow HGR
Color Index:	Pigment Yellow 191
C.I.No.	18795
CAS No.	129423-54-7
EC No.	403-530-4
Chemical Nature:	Mono azo
Chemical Formula	$C_{17}H_{13}CaClN_4O_7S_2$

Technical Properties:

A brilliant yellow pigment, with excellent heat resistance, good migration resistance, good weather, light fastness.

Application:

Recommend: PVC, EVA, Fiber, RUB, PP, PE and powder coating.

Suggested for PU, PC, PS, PA and water based paints.

Physical Properties

Appearance	Yellow powder
Color Shade	Reddish shade
Density(g/cm3)	1.6
Water Soluble Matter	≤1.0
Coloring Strength	100% ± 5
PH Value	6.5-7.5
Oil Absorption	35-45
Acid Resistance	5
Alkali Resistance	5
Heat Resistance	300°C
Migration Resistance	5 (1-5, 5 is excellent)

Resistance			Recommended applications							
Heat °C	Light	Migration	PVC	PU	RUB	Fiber	EVA	PP	PE	PS.PC.PA
300	7~8	5	●	○	●	●	●	●	●	○

Note: The above information is provided as guidelines for your reference only.
The accurate effects should base on the test results in laboratory.