HANGZHOU HANHAO CHEMICAL CO., LTD

Plant: Jiangdong Development Zone, Great Jiangdong District, Hangzhou China **Office:** 2103 Bldg1, Dacheng Plaza, Shixin Road, Xiaoshan, Hangzhou, China **Tel:**+86-571-82502631/82551631 **Fax:**+86-571-82722631

TECHNICAL DATA SHEET

Product Description:

Product Name: Fast Yellow TRP-G
Color Index: Pigment Yellow 62

C.I.No. 13940 CAS No. 12286-66-7 EC No. 235-558-4

Chemical Nature: Azo

Chemical Formula C₃₄H₃₀CaN₈O₁₄S₂

Technical Properties:

A greenish & reddish pigment powder, with good migration, high light fastness and heat resistance.

Application:

Recommend: PVC, RUB, PP, PE, EVA, Industrial paints and water based paints. Suggested for ABS, solvent based decorative paints, coil coatings.

Physical Properties

Appearance	Yellow powder				
Color Shade	Greenish & Reddish shade				
Density(g/cm3)	5.5-6.5				
Water Soluble Matter	≤1.5				
Coloring Strength	100% ±5				
PH Value	6.0-7.0				
Oil Absorption	35-45				
Acid Resistance	5				
Alkali Resistance	5				
Heat Resistance	200℃				
Migration Resistance	$4\sim5$ (1-5, 5 is excellent)				

Resistance			Recommended applications							
Heat °C	Light	Migration	PVC	PU	RUB	Fiber	EVA	PP	PE	PS.PC.PA
200	5~6	4~5	•		•		•	•	•	0

Note: The above information is provided as guidelines for your reference only. The accurate effects should base on the test results in laboratory.