# HANGZHOU HANHAO CHEMICAL CO., LTD

**Plant:** Jiangdong Development Zone, Great Jiangdong District, Hangzhou China **Office:** 2103 Bldg1, Dacheng Plaza, Shixin Road, Xiaoshan, Hangzhou, China **Tel:**+86-571-82502631/82551631 **Fax:**+86-571-82722631

#### TECHNICAL DATA SHEET

### **Product Description:**

Product Name: Light Chrome Yellow D203

Color Index: Pigment Yellow 34

C.I.No. 77603 CAS No. 7758-97-6 EC No. 215-693-7

Chemical Nature: Inorganic Pigment

Chemical Formula CrO<sub>4</sub>Pb

### **Technical Properties:**

It is Bright color, strong tinting strength, high hiding with good light fastness and dispersibility

#### **Application:**

Recommend: Inks, Coatings, Plastic and Rubber

#### **Color Shade and tinting strength**

Item				Standard
	Minimum	Maximu	m	Test way
Binding Materials	The refined li	inseed oil (4)		
Color Shade	Similar			DIN ISO787 Part 1; GB/T 1864
<b>Tinting Shade</b>	Similar			GB/T 5211.19
Binder	Offset printing ink resin(10-40 white)			
<b>Tinting Strength</b>	95		A	No.038,2009-08-01;GB/T5211.19

#### **Technical Data**

Item	Minimum	Maximum	Test way
Water Soluble Matter		1.0	DIN ISO787 Part 3;GB/T 5211.1
PH value	4	8.0	DIN ISO787 Part 9;GB/T 1717
<b>Volatile Matter 105℃</b>		2.0	DIN ISO787 Part 2;GB/T 5211.3
Oil Absorption (g /		30.0	DIN ISO787 Part 5;GB/T 5211.15
100g)			

Note: The above information is provided as guidelines for your reference only. The accurate effects should base on the test results in laboratory.

## **Transport and storage**

During transport should prevent rain, sunlight exposure, loading and unloading must be light, light relief, prevents breakage, obey the traffic rules. Product should be stored in ventilated, dry and cool warehouse, must be isolated from the acid, alkali and other chemicals and flame. Package products have been opened: sealed packaging in order to prevent absorption of moisture and contamination..

